

## Product card BNC-114

---



|                        |                |
|------------------------|----------------|
| <b>Symbol:</b>         | BNC-114        |
| <b>Product groups:</b> | BNC connectors |

### Product specifications

|                                    |                       |
|------------------------------------|-----------------------|
| <b>Type of connector:</b>          | BNC                   |
| <b>Connector:</b>                  | plug                  |
| <b>Kind of connector:</b>          | male                  |
| <b>Spatial orientation:</b>        | straight              |
| <b>Wave impedance:</b>             | 93Ω                   |
| <b>Max. cable diameter:</b>        | 2.8mm                 |
| <b>Electrical mounting:</b>        | crimped               |
| <b>Kind of cable:</b>              | RG179, RGB VideoKabel |
| <b>Mechanical mounting:</b>        | for cable             |
| <b>Mechanical durability:</b>      | 100 cycles            |
| <b>Manufacture class:</b>          | industrial            |
| <b>Contact plating:</b>            | gold-plated           |
| <b>Plating thickness:</b>          | 0.8μm                 |
| <b>Min. insulation resistance:</b> | 5GΩ                   |
| <b>Rated voltage:</b>              | 0.5kV                 |

**Max. frequency:** 2GHz

## **Additional information**

**Gross weight:** 0.011 kg