

## Product card KS-47

---



image not found or type unknown

|                        |                        |
|------------------------|------------------------|
| <b>Symbol:</b>         | KS-47                  |
| <b>Product groups:</b> | Key Switches and Locks |

### Product specifications

|                                   |   |
|-----------------------------------|---|
| <b>Type of switch:</b>            | key switch  |
| <b>Stable positions number:</b>   | 2   |
| <b>Switching method:</b>          | OFF-ON  |
| <b>Contacts configuration:</b>    | SPST  |
| <b>Switches features:</b>         | key with the random code, the key can be removed at left limit position |
| <b>Number of positions:</b>       | 2   |
| <b>Mounting hole diameter:</b>    | Ø16mm   |
| <b>Key shape:</b>                 | flat  |
| <b>Kind of wrench:</b>            | unsymmetrical   |
| <b>Body material:</b>             | zinc alloy  |
| <b>AC contacts rating @R:</b>     | 1A / 125V AC  |
| <b>Mechanical rotation angle:</b> | 90°   |
| <b>Number of terminals:</b>       | 2   |

|                           |               |
|---------------------------|---------------|
| <b>Overall length:</b>    | 31mm          |
| <b>Terminals plating:</b> | silver plated |
| <b>Contact plating:</b>   | silver plated |

## **Additional information**

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.028 kg |
|----------------------|----------|