



| | |
|----------------|--------|
| Symbol: | NXW-05 |
|----------------|--------|

| | |
|------------------------|--------------------------|
| Product groups: | Raster signal connectors |
|------------------------|--------------------------|

Product specifications

| | |
|---------------------------|------------|
| Type of connector: | wire-board |
|---------------------------|------------|

| | |
|-------------------|--------|
| Connector: | socket |
|-------------------|--------|

| | |
|---------------------------|------|
| Kind of connector: | male |
|---------------------------|------|

| | |
|------------------------|---|
| Number of pins: | 5 |
|------------------------|---|

| | |
|-----------------------------|----------|
| Spatial orientation: | straight |
|-----------------------------|----------|

| | |
|-----------------------------|-----|
| Electrical mounting: | THT |
|-----------------------------|-----|

| | |
|------------------------|-----|
| Contacts pitch: | 2mm |
|------------------------|-----|

| | |
|---------------------------------|-----|
| Connector pinout layout: | 1x5 |
|---------------------------------|-----|

| | |
|-------------------------|--------|
| Contact plating: | tinned |
|-------------------------|--------|

| | |
|-----------------------------|---------|
| Flammability rating: | UL94V-0 |
|-----------------------------|---------|

| | |
|----------------------------------|------------|
| Maximum current: | 1A |
| Max. operating voltage: | 100V |
| Max. contact resistance:: | 20mΩ |
| Enclosure material: | polyamide |
| Width: | 12.1mm |
| Operating temperature: | -25...85°C |

Additional information

| | |
|----------------------|------|
| Gross weight: | 0 kg |
|----------------------|------|