



|                        |                   |
|------------------------|-------------------|
| <b>Symbol:</b>         | PS11ARD           |
| <b>Product groups:</b> | Standard Switches |

## Product specifications

|                                 |               |
|---------------------------------|---------------|
| <b>Type of switch:</b>          | push-button   |
| <b>Number of positions:</b>     | 2             |
| <b>Stable positions number:</b> | 2             |
| <b>Contacts configuration:</b>  | SPST-NO       |
| <b>AC contacts rating @R:</b>   | 1A / 250V AC  |
| <b>Switching method:</b>        | OFF-ON        |
| <b>Illumination:</b>            | none          |
| <b>Leads:</b>                   | for soldering |

## Product card PS11ARD

---

|                                  |              |
|----------------------------------|--------------|
| <b>Electrical life:</b>          | 50000 cycles |
| <b>Max. contact resistance::</b> | 20mΩ         |
| <b>Button shape:</b>             | round        |
| <b>Mounting hole diameter:</b>   | Ø12mm        |
| <b>Body colour:</b>              | black        |
| <b>Actuator colour:</b>          | red          |
| <b>Mounting:</b>                 | on panel     |
| <b>Operating temperature:</b>    | -25...70°C   |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.006 kg |
|----------------------|----------|