



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | SR17B1415F49N   |
| <b>Product groups:</b> | Rotary Switches |

## Product specifications

|                                    |                    |
|------------------------------------|--------------------|
| <b>Type of switch:</b>             | rotary             |
| <b>Number of positions:</b>        | 4                  |
| <b>Stable positions number:</b>    | 4                  |
| <b>DC contacts rating @R:</b>      | 0.3A / 16V DC      |
| <b>Poles number:</b>               | 1                  |
| <b>Indexed positions:</b>          | 30°                |
| <b>Leads:</b>                      | angled, for PCB    |
| <b>Contact material:</b>           | brass              |
| <b>Switching method:</b>           | BBM (non-shorting) |
| <b>Max. contact resistance::</b>   | 50mΩ               |
| <b>Body material:</b>              | steel              |
| <b>Min. insulation resistance:</b> | 0.1GΩ              |
| <b>Mechanical durability:</b>      | 10000 cycles       |
| <b>Shaft surface:</b>              | smooth             |

|                               |            |
|-------------------------------|------------|
| <b>Shaft diameter:</b>        | 6mm        |
| <b>Shaft length:</b>          | 7mm        |
| <b>Fastening thread:</b>      | M9x0,75    |
| <b>Switching torque:</b>      | 2.9Ncm     |
| <b>Operating temperature:</b> | -20...70°C |

## **Additional information**

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.009 kg |
|----------------------|----------|