



**Symbol:** SR2611815FN

**Product groups:** Rotary Switches

## Product specifications

|                                 |                    |
|---------------------------------|--------------------|
| <b>Type of switch:</b>          | rotary             |
| <b>Number of positions:</b>     | 8                  |
| <b>Stable positions number:</b> | 8                  |
| <b>AC contacts rating @R:</b>   | 0.3A / 125V AC     |
| <b>Poles number:</b>            | 1                  |
| <b>Indexed positions:</b>       | 30°                |
| <b>Leads:</b>                   | for soldering      |
| <b>Contact material:</b>        | brass              |
| <b>Switching method:</b>        | BBM (non-shorting) |

|                                    |             |
|------------------------------------|-------------|
| <b>Max. contact resistance::</b>   | 30mΩ        |
| <b>Min. insulation resistance:</b> | 0.1GΩ       |
| <b>Mechanical durability:</b>      | 6000 cycles |
| <b>Shaft surface:</b>              | smooth      |
| <b>Shaft diameter:</b>             | 6mm         |
| <b>Shaft length:</b>               | 15mm        |
| <b>Fastening thread:</b>           | 3/8"-32NEF  |
| <b>Switching torque:</b>           | 4.9Ncm      |
| <b>Operating temperature:</b>      | -20...70°C  |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.009 kg |
|----------------------|----------|