



**Symbol:** TBG-5-PW-3P/GN

**Product groups:** Terminal blocks

## Product specifications

**Type of connector:** pluggable terminal block

**Connector:** socket

**Kind of connector:** male

**Current rating:** 15A

**Rated voltage:** 0.3kV

**Number of pins:** 3

**Spatial orientation:** straight

**Mechanical mounting:** on PCBs

**Electrical mounting:** THT

**Contact material:** brass

|                                 |             |
|---------------------------------|-------------|
| <b>Contact plating:</b>         | tinned      |
| <b>Colour:</b>                  | green       |
| <b>Flammability rating:</b>     | UL94V-0     |
| <b>Body material:</b>           | polyamide   |
| <b>Depth:</b>                   | 8mm         |
| <b>Connector pinout layout:</b> | 1x3         |
| <b>Contacts pitch:</b>          | 5.08mm      |
| <b>Number of ways:</b>          | 3           |
| <b>Locking system:</b>          | for latch   |
| <b>Height:</b>                  | 11.9mm      |
| <b>Soldering temperature:</b>   | 250°C / 5 s |
| <b>Operating temperature:</b>   | -40...105°C |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.001 kg |
|----------------------|----------|