

## Product card TSM202E1

---



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | TSM202E1        |
| <b>Product groups:</b> | Toggle Switches |

### Product specifications

|                                  |                 |
|----------------------------------|-----------------|
| <b>Type of switch:</b>           | toggle          |
| <b>Number of positions:</b>      | 2               |
| <b>Stable positions number:</b>  | 2               |
| <b>Contacts configuration:</b>   | DPDT            |
| <b>Switching method:</b>         | ON-ON           |
| <b>AC contacts rating @R:</b>    | 3A / 250V AC    |
| <b>Leads:</b>                    | for soldering   |
| <b>Operating temperature:</b>    | -25...85°C      |
| <b>Kind of toggle:</b>           | flat            |
| <b>Mounting hole diameter:</b>   | Ø6.2mm          |
| <b>Knob height:</b>              | 13.5mm          |
| <b>Max. contact resistance::</b> | 20mΩ            |
| <b>Body dimensions:</b>          | 13.2x12.9x9.5mm |

## Product card TSM202E1

---

|                               |              |
|-------------------------------|--------------|
| <b>Electrical life:</b>       | 20000 cycles |
| <b>Actuator material:</b>     | plastic      |
| <b>Body colour:</b>           | blue         |
| <b>Soldering temperature:</b> | 260°C / 4 s  |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.006 kg |
|----------------------|----------|