



|                |            |
|----------------|------------|
| <b>Symbol:</b> | ZL264-34DG |
|----------------|------------|

|                        |             |
|------------------------|-------------|
| <b>Product groups:</b> | Pin headers |
|------------------------|-------------|

## Product specifications

|                           |            |
|---------------------------|------------|
| <b>Type of connector:</b> | pin strips |
|---------------------------|------------|

|                   |        |
|-------------------|--------|
| <b>Connector:</b> | socket |
|-------------------|--------|

|                           |        |
|---------------------------|--------|
| <b>Kind of connector:</b> | female |
|---------------------------|--------|

|                        |    |
|------------------------|----|
| <b>Number of pins:</b> | 34 |
|------------------------|----|

|                             |     |
|-----------------------------|-----|
| <b>Electrical mounting:</b> | SMT |
|-----------------------------|-----|

|                             |          |
|-----------------------------|----------|
| <b>Spatial orientation:</b> | vertical |
|-----------------------------|----------|

|                        |        |
|------------------------|--------|
| <b>Contacts pitch:</b> | 2.54mm |
|------------------------|--------|

|                                 |      |
|---------------------------------|------|
| <b>Connector pinout layout:</b> | 2x17 |
|---------------------------------|------|

|                         |             |
|-------------------------|-------------|
| <b>Contact plating:</b> | gold-plated |
|-------------------------|-------------|

**Operating  
temperature:**

-55...105°C

## **Additional information**

**Gross weight:**

0.002 kg