

|                        |                    |
|------------------------|--------------------|
| <b>Symbol:</b>         | TACT-617N-F        |
| <b>Product groups:</b> | Microswitches TACT |

## Product specifications

|                                 |                  |
|---------------------------------|------------------|
| <b>Type of switch:</b>          | microswitch TACT |
| <b>Contacts configuration:</b>  | SPST-NO          |
| <b>Number of positions:</b>     | 2                |
| <b>Stable positions number:</b> | 1                |
| <b>DC contacts rating @R:</b>   | 50mA / 12V DC    |
| <b>Mounting:</b>                | SMT              |
| <b>Illumination:</b>            | none             |
| <b>Operating Force:</b>         | 1.6N             |
| <b>Body dimensions:</b>         | 6x6mm            |
| <b>Button height:</b>           | 19mm             |
| <b>Switching method:</b>        | OFF-(ON)         |
| <b>Operating temperature:</b>   | -25...70°C       |
| <b>Button shape:</b>            | round            |
| <b>Actuator colour:</b>         | black            |
| <b>Leads:</b>                   | for PCB          |

|                                  |      |
|----------------------------------|------|
| <b>Max. contact resistance::</b> | 50mΩ |
|----------------------------------|------|

|                                    |       |
|------------------------------------|-------|
| <b>Min. insulation resistance:</b> | 0.1GΩ |
|------------------------------------|-------|

|                               |       |
|-------------------------------|-------|
| <b>Soldering temperature:</b> | 235°C |
|-------------------------------|-------|

## **Additional information**

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.005 kg |
|----------------------|----------|