



|                        |                    |
|------------------------|--------------------|
| <b>Symbol:</b>         | TACTM-63N-F        |
| <b>Product groups:</b> | Microswitches TACT |

## Product specifications

|                                 |                  |
|---------------------------------|------------------|
| <b>Type of switch:</b>          | microswitch TACT |
| <b>Contacts configuration:</b>  | SPST-NO          |
| <b>Number of positions:</b>     | 2                |
| <b>Stable positions number:</b> | 1                |
| <b>DC contacts rating @R:</b>   | 50mA / 12V DC    |
| <b>Mounting:</b>                | SMT              |
| <b>Illumination:</b>            | none             |
| <b>Operating Force:</b>         | 1.6N             |

|                               |            |
|-------------------------------|------------|
| <b>Body dimensions:</b>       | 6.2x6.2mm  |
| <b>Button height:</b>         | 3.1mm      |
| <b>Switching method:</b>      | OFF-(ON)   |
| <b>Terminal pitch:</b>        | 4.5x8.5mm  |
| <b>Operating temperature:</b> | -25...70°C |
| <b>Button shape:</b>          | round      |
| <b>Leads:</b>                 | for PCB    |

## Additional information

|                      |      |
|----------------------|------|
| <b>Gross weight:</b> | 0 kg |
|----------------------|------|